



Spirit of Adventure

SPRITE CARAVANS

Dunswell Road, Cottingham, East Yorkshire, HU16 4JX.

Tel: 01482 875740 Fax: 01482 840082

email: enquiry@swiftleisure.co.uk

website: www.spritecaravans.co.uk

A MEMBER OF THE SWIFT GROUP

1079651 v2 issued January 2008



Spirit of Adventure

SPECIFICATION, WIRING DIAGRAMS & BULB CHART





CONTENTS

Specification	1
Wiring Diagrams - 230V Circuits	2
Wiring Diagrams - Power Circuits	3
Wiring Diagrams - Consumer Circuits – Floor	4
Wiring Diagrams - Consumer Circuits – Roof	5
Wiring Diagrams - Road Lighting	6
Wiring Diagrams - Cable Color Chart.....	7
Wiring Diagrams - Fuses	8
Bulb Replacement	9


Specifications

	ALPINE 2		ALPINE 4		MAJOR 5	MAJOR 6	QUATTRO ES	QUATTRO FB
Berths	2		4		5	6	6	6
Axles	1		1		1	1	2	2
Internal Length (bed box height)	4.34m/14'3"		4.74m/15'7"		5.03m/16'6"	5.50m/18'1"	6.27m/20'7"	6.27m/20'7"
Overall Width	2.23m/7'4"		2.23m/7'4"		2.23m/7'4"	2.23m/7'4"	2.23m/7'4"	2.23m/7'4"
Overall Height (inc. TV Aerial)	2.70m/8'10"		2.70m/8'10"		2.70m/8'10"	2.70m/8'10"	2.70m/8'10"	2.70m/8'10"
Maximum Internal Headroom	1.95m/6'5"		1.95m/6'5"		1.95m/6'5"	1.95m/6'5"	1.95m/6'5"	1.95m/6'5"
Overall Length	5.99m/19'8"		6.40m/21'0"		6.68m/21'11"	7.15m/23'5"	7.91m/25'11"	7.91m/25'11"
Mass in Running Order (inc. tolerance)	973kg/19.2cwt		999kg/19.7cwt		1101kg/21.7cwt	1176kg/23.1cwt	1319kg/26.0cwt	1296kg/25.5cwt
Essential Habitation Equipment Payload	68kg/1.3cwt		68kg/1.3cwt		68kg/1.3cwt	68kg/1.3cwt	68kg/1.3cwt	68kg/1.3cwt
Personal Effects Payload	101kg/2.0cwt		125kg/2.5cwt		138kg/2.7cwt	153kg/3.0cwt	160kg/3.1cwt	160kg/3.1cwt
Optional Equipment Payload	28kg/0.6cwt		28kg/0.6cwt		28kg/0.6cwt	28kg/0.6cwt	28kg/0.6cwt	31kg/0.6cwt
Total user Payload	197kg/3.9cwt		221kg/4.4cwt		234kg/4.6cwt	249kg/4.9cwt	256kg/5.0cwt	259kg/5.0cwt
Maximum Technical Permissible Laden Mass (DECLARED)	1170kg/23.1cwt		1220kg/24.1cwt		1335kg/26.3cwt	1425kg/28.0cwt	1575kg/31.0cwt	1555kg/30.5cwt
Maximum Technical Permissible Laden Mass (POSSIBLE)	1200kg/23.6cwt		1250kg/24.6cwt		1500kg/29.5cwt	1500kg/29.5cwt	1600kg/31.5cwt	1600kg/31.5cwt
Awning A/A dimension†	8.55m/28'1"		8.95m/29'4"		9.24m/30'4"	9.71m/31'10"	10.48m/34'5"	10.48m/34'5"
Tyre Size**	195/70 r14 96	175 r14 99	195/70 r14 96	175 r14 99	175 r14 99	175 r14 99	175/65 r14 82	175/65 r14 82
Tyre pressure at DECLARED MTPLM**	36 psi	44 psi	36 psi	51 psi	58psi	62psi	30psi	30psi
Tyre pressure at POSSIBLE MTPLM**	36 psi	51 psi	40 psi	55 psi	65psi	65psi	34psi	34psi
Static Load on Coupling Head	100kg		100kg		100kg	100kg	100kg	100kg
Thermal Insulation Grade	TWO		TWO		TWO	TWO	TWO	TWO
Bed Sizes								
Front Double	208cm x 180cm/6'10" x 5'11"		208cm x 134cm/6'10" x 4'5"		208cm x 180cm/6'10" x 5'11"	208cm x 180cm/6'10" x 5'11"	208cm x 180cm/6'10" x 5'11"	208cm x 180cm/6'10" x 5'11"
or Front Single (nearside)	190cm x 72cm/6'3" x 2'4"				180cm x 72cm/5'11" x 2'4"	190cm x 72cm/6'3" x 2'4"	190cm x 72cm/6'3" x 2'4"	180cm x 72cm/5'11" x 2'4"
or Front Single (offside)	180cm x 72cm/5'11" x 2'4"				190cm x 72cm/6'3" x 2'4"	180cm x 72cm/5'11" x 2'4"	180cm x 72cm/5'11" x 2'4"	190cm x 72cm/6'3" x 2'4"
Rear Double			188cm x 138cm/6'2" x 4'6"		208cm x 124cm/6'10" x 4'1"			192cm x 133cm/6'3"x 4'4"
Rear Bunk					190cm x 56cm/6'3" x 1'10"			
Side Bunk						178cm x 59cm/5'10" x 1'11"	178cm x 59cm/5'10" x 1'11"	178cm x 59cm/5'10" x 1'11"
Rear Lower Bunk						180cm x 62cm/5'11" x 2'1"		
Rear Upper Bunk						184cm x 60cm/6'0" x 2'0"		
Side Single (nearside)						180cm x 70cm/5'11" x 2'4"	180cm x 70cm/5'11" x 2'4"	
Side Single (offside)								180cm x 70cm/5'11" x 2'4"
Side Fixed Lower Bunk							180cm x 56cm/5'11" x 1'10"	
Side Fixed Upper Bunk							180cm x 58cm/5'11" x 1'11"	

Bed sizes: Please note that double bed sizes are quoted with wrap round seating.
†**Note on awning sizes:** Due to the varying awning designs and sizes the awning sizes given are approximate only. Specific awning sizes must be confirmed by your dealer or the awning manufacturer prior to purchase.
**Check the loading on the side wall of the tyre before adjusting tyre pressure, replacing or purchasing a spare wheel and tyre. All tyres on the caravan must be of an identical size and load rating.


Wiring Diagrams

SPRITE RANGE - 230V CIRCUITS




Wiring Diagrams


SPRITE RANGE - POWER CIRCUITS




SPRITE RANGE - CONSUMER CIRCUITS – FLOOR




SPRITE RANGE - CONSUMER CIRCUITS – ROOF



SPRITE RANGE - ROAD LIGHTING




SPRITE RANGE - CABLE COLOUR CHART



Wiring Diagrams

SPRITE RANGE - FUSE BOX SCHEMATIC



Bulb Replacement

	TYPE	RATING	SPRITE		
ROAD LIGHTS					
Front marker lights	W5W	12v 5w	✓		
Side marker	C5W	12v 5w	✓		
Reversing light	P21	12v 21w	✓		
Rear indicator light	PY21W Orange bulb	12v 21w	✓		
Brake/tail light	P21/5W	12v 21w/5w	✓		
Fog light	P21	12v 21w	✓		
Number plate light	C5W	12v 5w	✓		
INTERIOR/OTHER					
Awning light	P21W	12v 20w	✓		
Spot/reading lights	GU4/MR11 Dichroic	GU4 12v 10w	✓		
Ceiling light, round	Halogen capsule	G4 12v 20w	✓		
Ceiling light, small round white	Halogen capsule	G4 12v 10w	✓		
Down lighters	Halogen capsule	G4 12v 10w	✓		

Note: Not all bulbs and lights feature on all models within a range